




TRANSHOW INDUSTRY LIMITED

GAOYANG RD, ZHOUSHAN VILLAGE, JIANGSHAN TOWN
 YINZHOU DISTRICT, NINGBO CITY, 315100 CHINA
 Tel: +86-574-8736.7873 Fax: +86-574-8736.4349
www.transhow.net Email: transhow@transhow.net

Self Clinching Nut-Inch Specifications



All dimensions in inch standard

Size	A	Minimum Sheet Thickness	Hole Size in 0.003	C	E	T
	Shank Hgt. Max.			Shank Diam. Max.	Nut Dia.	Nut Hgt. Max.
4-40-0	0.030	.030-.039	0.166	0.165	0.25	0.07
4-40-1	0.038	0.040	0.166	0.165	0.25	0.07
4-40-2	0.054	0.056	0.160	0.165	0.25	0.07
6-32-0	0.030	.030-.039	0.188	0.187	0.28	0.07
6-32-1	0.038	0.040	0.188	0.187	0.28	0.07
6-32-2	0.054	0.056	0.188	0.187	0.28	0.07
8-32-0	0.030	.030-.039	0.213	0.212	0.31	0.09
8-32-1	0.038	0.040	0.213	0.212	0.31	0.09
8-32-2	0.054	0.056	0.213	0.212	0.31	0.09
10-24-0	0.030	.030-.039	0.250	0.249	0.34	0.09
10-24-1	0.038	0.040	0.250	0.249	0.34	0.09
10-24-2	0.054	0.056	0.250	0.249	0.34	0.09
10-32-0	0.030	.030-.039	0.250	0.249	0.34	0.09
10-32-1	0.038	0.040	0.250	0.249	0.34	0.09
10-32-2	0.054	0.065	0.250	0.249	0.34	0.09
1/4-20-1	0.054	0.056	0.344	0.343	0.44	0.17
1/4-20-2	0.087	0.091	0.344	0.343	0.44	0.17